


PCB LAYOUT

4	Screw	Steel	M3/Zn Plated
3	Cage	Copper alloy	M3/Ni Plated
2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/300	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category /污染等级 / Pollution Degree	III/2		
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/32		
工频耐压/Withstanding voltage(V/1Min)	AC3500		
螺栓扭矩/Torque Tightening(N·m/Lb·in)	M3, 0.5/4.43		
线径范围 (硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~4.0mm ² (str) 0.2~6.0mm ² (sol) /26~10		
间距/Pitch(mm)/线数范围/Poles	9.52/N=2~24P		
剥线长度/Stripping length(mm)	8~9		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

SURFACE:



NAME: SA635-9.52-XXP-1Y-00A(H)

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	

SIZE: A4	mm
	(inch)

DRAWING NO.:	SCALE:	REV
TYPE:	SHEET	1/1

公差/General tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10	±Z
--------	----